



NOTCH LOCK



Flexible Connector

DESCRIPTION

Elgen's Notch Lock eliminates duct system noises and vibrations. This is done with an airtight flexible connection consisting of a fabric that attaches to sheet metal on both sides

BASIC USE

Elgen's Notch Lock Flexible Connector attaches to a fan sources on one side and ductwork on the other.



SPECIAL CHARACTERISTICS

- All Elgen fabrics are designed to meet NFPA-701 (formerly UL-214)
- 2 GA With 40 oz Neoprene Tested At 23" Positive Static Pressure
- Elgen Vinlon fabric meets UL-723 and NFPA-701
- All Elgen fabrics are designed to meet NFPA-90A and 90B
- All fabrics are water proof and airtight to +/- 10"w.g.
- All fabrics have flame retardant coatings
- All items are Flame Resistant
- Tested in accordance with LEEDS®
- Requirements Meets SMACNA
- Made with Domestic Galvanized Steel
- Union Made

	Vinlon	Neoprene
Temp Range	-40° F to 180° F	-40° F to 280° F
Color	Black	Black
Weight SQ/YD	22	32
Tear Strength	100/100	25/25
Tensile Strength	300/300	500/500
Features	High tear strength, High Abrasion, Low Smoke, Extremely Flexible	Airtight resistance to acids, Gasoline & Grease, General Purpose

OPTIONAL CONSTRUCTION

G90	PCD
Stainless 304	Galvanneal
Stainless 316	Agion (Antimicrobial Coating)
Aluminum	

PACKAGING

Size	Gauge	FT Per Box
All Sizes	24-26	100'

LIST PRICES

3X3X3 Vinlon Notched Flex Connector	\$216.00 per roll
4X4X4 Vinlon Notched Flex Connector	\$260.00 per roll
3X3X3 Neoprene Notched Flex Connector	\$263.00 per roll
4X4X4 Neoprene Notched Flex Connector	\$320.00 per roll
1 3/4 x 3 x 1 3/4 Flex Connector	\$145.00 per roll